

What is claimed is:

1. A filter comprising:

a filter element;

a core member in fluid communication with the filter element; and

a sleeve of a substantially fluid non-permeable material surrounding at least a portion of one end of the filter element.

2. A filter of claim 1 wherein the sleeve surrounds substantially all of the filter element and has perforations through a portion of the sleeve with the perforations in the sleeve toward one end of the filter element.

3. A filter of claim 1 wherein the filter element comprises a material selected from pleated media and non-pleated media.

4. A filter of claim 3 wherein the non-pleated media is selected from the group comprising wrapped media, solid media and granular media.

5. A filter element of claim 3 wherein the pleated media comprises a material selected from the group comprising cellulose, polypropylene, polyethylene, polyester, fiberglass, cloth, paper, nylon, orlon, teflon and combinations thereof.

1 6. A filter element of claim 4 wherein the wrapped media comprises a material selected
2 from the group comprising spunbonded material, cloth, polypropylene, polyester and mixtures
3 thereof.

1 7. A filter element of claim 1 further comprising a rigid support surrounding the filter
2 element inside the sleeve.

1 8. A filter element of claim 1 wherein the rigid support further comprises a mesh.

1 9. A filter element of claim 1 wherein the core member comprises a rigid perforated
2 tube.

10. A filter comprising:
a housing with a fluid inlet and a fluid outlet;
a filter element disposed within the housing;
said filter element having a central core in fluid communication with the filter
element;
the fluid outlet of the housing in communication with the central core; and
a sleeve of a substantially fluid non-permeable material surrounding at least a
portion of one end of the filter element preventing fluid flow into the filter
element.

1 11. A filter of claim 10 wherein the fluid inlet of the housing is towards the end of the
2 filter surrounded by the sleeve.

1 12. A filter of claim 10 wherein the sleeve member surrounds substantially all of the filter
2 element and has perforations through a portion of the sleeve with the perforations in the sleeve
3 toward one end of the filter element and providing fluid communication to the filter element.

1 13. A filter of claim 10 further comprising a sleeve member which is joined to an end cap
2 on which the filter element abuts and has a central cylindrical extension in fluid communication with
the central core and has a seal member on the central cylindrical extension and is coupled to the
outlet of the housing.

14. A filter of claim 13 wherein the seal member further comprises a gasket, said gasket
configured to direct the fluid from the central core through the outlet of the housing.

1 15. A filter of claim 10 wherein the filter element comprises a material selected from
2 pleated media and non-pleated media.

1 16. A filter of claim 15 wherein the non-pleated media is selected from the group
2 comprising wrapped media, solid media and granular media.

1 17. A filter element of claim 16 wherein the pleated media comprises a material selected
2 from the group comprising cellulose, polypropylene, polyethylene, polyester, fiberglass, cloth,
3 paper, nylon, orlon, teflon and combinations thereof.

1 18. A filter element of claim 16 wherein the wrapped media comprises a material selected
2 from the group comprising spunbonded material, cloth, fiberglass, polypropylene, polyester and
3 mixtures thereof.

1 19. A filter element of claim 10 further comprising a rigid support surrounding the filter
element inside the sleeve.

20. A filter element of claim 19 wherein the rigid support further comprises a mesh.

21. A filter element of claim 10 wherein the central core comprises a rigid perforated
tube.

1 / 22. A filter comprising:
2 a cylindrical filter element of pleated filter media;
3 a perforated central core extending through and surrounded by the pleated filter
4 media;
5 a sleeve of substantially fluid non-permeable material surrounding the outside of the
6 pleated filter media;

1 the sleeve having perforations through one of the top and the bottom of the sleeve
2 capable of providing fluid communication to the filter element;
3 a circular top end cap covering and securing the sleeve, the top of the filter element
4 and the core; and
5 a circular bottom end cap with a central cylindrical extension in fluid communication
6 with the central core, said bottom cap securing and covering the sleeve and
7 the bottom of the filter element.

1 23. A filter of claim 22 further comprising a seal member on the central cylindrical
extension of the bottom end cap adaptable to be received in a filter housing to provide a substantially
leak-proof connection.

24. A filter comprising:
a filter element;
a core member in the filter element extending a partial length of the filter element
from one end of the filter element; and
5 said core member composed of a substantially fluid non-permeable material.

1 25. A filter of claim 24 wherein the core member extends substantially the length of the
2 filter and has fluid communication to the core member toward one end of the filter element.

1 26. A filter of claim 24 wherein the filter element comprises a material selected from
2 pleated media and non-pleated media.

1 27. A filter of claim 26 wherein the non-pleated media is selected from the group
2 comprising wrapped media, solid media and granular media.

1 28. A filter element of claim 26 wherein the pleated media comprises a material selected
2 from the group comprising cellulose, polypropylene, polyethylene, polyester, fiberglass, cloth,
3 paper, nylon, orlon, teflon and combinations thereof.

 29. A filter element of claim 27 wherein the wrapped media comprises a material selected
from the group comprising spunbonded material and cloth.

 30. A filter element of claim 24 further comprising a rigid support surrounding the filter
element which allows for fluid flow into the filter element.

1 31. A filter element of claim 30 wherein the rigid support further comprises a mesh.

1 32. A filter element of claim 24 wherein the core member comprises a rigid member.

1 33. A filter element of claim 32 wherein the central core is a rigid perforated cylindrical
2 member.

1 34. A filter comprising:
2 a housing with a fluid inlet;
3 a filter element disposed within the housing;
4 said filter element having a central core with a fluid non-permeable portion toward
5 one end of the filter and the central core in fluid communication with the
6 filter element on the other end of the filter;
7 said housing having a fluid inlet in communication with the central core; and
8 said housing having a fluid outlet.

35. A filter of claim 34 wherein the central core extends the length of the filter and has perforations through a portion of the central core toward one end of the filter element.

36. A filter of claim 34 wherein the central core is joined to an end cap on which the filter element abuts and which end cap has a central cylindrical extension in fluid communication with the central core and has a seal member on the outside of the central cylindrical extension which is coupled to the inside of the inlet of the housing.

1 37. A filter of claim 36 wherein the seal member further comprises a gasket, said gasket
2 configured to direct the fluid into the filter element.

1 38. A filter of claim 34 wherein the filter element comprises a material selected from
2 pleated media and non-pleated media.

39. A filter of claim 38 wherein the non-pleated media is selected from the group comprising wrapped media, solid media and granular media.

40. A filter element of claim 38 wherein the pleated media comprises a material selected from the group comprising cellulose, polypropylene, polyethylene, polyester, fiberglass, cloth, paper, nylon, orlon, teflon and combinations thereof.

41. A filter element of claim 39 wherein the wrapped media comprises a material selected from the group comprising spunbonded media and cloth.

42. A filter element of claim 34 further comprising a rigid support surrounding the filter element.

43. A filter element of claim 42 wherein the rigid support comprises a mesh.

44. A filter element of claim 34 further comprising a top cap which covers the top of the central core.

45. A method of filter fluids comprising the steps of:

flowing at least two fluids into a housing;

passing the fluids around a filter element partially surrounded by an a non-permeable barrier at the lower end of the filter element;

